

SensorsX

SX-CCFNA Series

Four-Electrode Conductivity (Salinity) Sensor

Industrial Conductivity / Salinity Sensor



0.001-100 mS/cm Conductivity Range	0-80 ppt Salinity Range	0-64,000 mg/L TDS Range
IP68 Ingress Protection	DC 9-24 V, >500 mA Power Supply	0.2 W Power Consumption

Industrial Water Quality Measurement | Conductivity / Salinity

■ PRODUCT OVERVIEW

The SX-CCFNA Series online conductivity/salinity sensor uses advanced four-electrode measurement technology with an RS-485 digital interface and Modbus protocol support. Compared with traditional two-electrode sensors, it provides higher accuracy, a wider measurement range, and improved stability. It is widely used in surface water, municipal wastewater, industrial wastewater, wastewater treatment, industrial process water, and aquaculture.



■ KEY FEATURES

- | | |
|---|---|
| ◆ RS-485 communication interface, standard Modbus protocol, for easy integration | ◆ Simultaneous output of conductivity, salinity, TDS, and temperature |
| ◆ Corrosion-resistant housing, IP68 waterproof rating, suitable for long-term submersible operation | ◆ Built-in temperature sensor with automatic temperature compensation |
| ◆ Built-in calibration parameters, factory-calibrated for quick installation and commissioning | |

■ TYPICAL APPLICATIONS

- Surface water monitoring
- Wastewater treatment
- Municipal wastewater
- Industrial process water
- Industrial wastewater
- Aquaculture

■ PERFORMANCE SPECIFICATIONS

Measurement	
Product Type	Conductivity (Salinity) Sensor
Measurement Principle	Four-electrode technology
Conductivity Range	0.001-5 mS/cm or 0.001-100 mS/cm
Salinity Range	0-2.5 ppt or 0-80 ppt
TDS Range	0-3,200 mg/L or 0-64,000 mg/L
Accuracy	
Conductivity Accuracy	±1% or 0.01 mS/cm (whichever is greater)
Salinity Accuracy	±0.05 ppt or ±1 ppt
Calibration	
Calibration	1-point or 2-point calibration

※ The technical specifications above are based on laboratory standard-solution conditions.

■ ELECTRICAL SPECIFICATIONS

Digital Communication	
Digital Interface	RS-485
Communication Protocol	Modbus
Power	
Power Consumption	0.2 W
Power Supply	DC 9-24 V, >500 mA

■ ENVIRONMENTAL SPECIFICATIONS

Temperature	
Operating Temperature Range	0-50 °C (32-122 °F)
Mechanical & Environmental	
Ingress Protection	IP68
Dimensions	Φ22 mm × 175.5 mm (Φ0.87 in × 6.91 in)
Cable Length	10 m (32.8 ft) default, customizable
Housing Material	Nickel + PEEK + Titanium Alloy

■ COMMUNICATION PROTOCOLS

Digital Interface	RS-485
Communication Protocol	Modbus

■ ORDERING INFORMATION

Complete model number reference: **SX-CCFNA-11111**

Conductivity Measurement Range

1	0.001-5 mS/cm
2	0.001-100 mS/cm

Conductivity Accuracy

1	±1% or 0.01 mS/cm (whichever is greater)
---	--

Salinity (SAL) Measurement Range

1	0-2.5 ppt
2	0-80 ppt

Salinity (SAL) Accuracy

1	±0.05 ppt
2	±1 ppt

TDS Measurement Range

1	0-3,200 mg/L
2	0-64,000 mg/L

Customized

D	Customized — specify requirements when ordering
---	---