

SensorsX SX-CNLNA Series

NH₄-N Ammonium Sensor (Brushless)
Industrial Ammonia Nitrogen Sensor



0-100 mg/L NH ₄ -N Range	±10% or ±0.5 mg/L NH ₄ -N Accuracy	4-10 pH pH Range
IP68 Ingress Protection	DC 9-24 V, ≥1 A Power Supply	0.25 W Power Consumption

Industrial Water Quality Measurement | Ammonia Nitrogen

■ PRODUCT OVERVIEW

The SX-CNLNA Series online ammonia-nitrogen sensor requires no reagents and generates no chemical waste, enabling real-time online monitoring. It is equipped with an ammonium-ion electrode, pH electrode, and reference electrode as standard, with an optional potassium-ion electrode. Automatic pH and temperature compensation helps improve measurement accuracy. The sensor supports direct immersion installation and provides a cost-effective solution for online ammonia-nitrogen monitoring. RS-485 output with Modbus protocol enables convenient system integration.



■ KEY FEATURES

◆ Digital sensor with RS-485 output, Modbus protocol	◆ No reagents required; no chemical waste; cost-effective and environmentally friendly
◆ Automatic pH and temperature compensation	◆ Ion-selective electrode method; no electrolyte solution required; electrodes can be individually replaced for easy maintenance
◆ Built-in calibration parameters for convenient field use and recalibration	

■ TYPICAL APPLICATIONS

- Real-time online ammonia-nitrogen monitoring in water and wastewater treatment

■ PERFORMANCE SPECIFICATIONS

Measurement	
Product Type	Ammonia-Nitrogen Sensor (Brushless)
Measurement Principle	Ion-selective electrode method
NH ₄ -N (Ammonia Nitrogen) Range	0-100 mg/L (0-1,000 mg/L optional)
pH Measurement Range	4-10 pH
Accuracy	
NH ₄ -N Accuracy	±10% or ±0.5 mg/L (whichever is greater)
Resolution	0.01 mg/L
Calibration	
Calibration	1-point or 2-point calibration

※ The technical specifications above are based on laboratory standard-solution conditions.

■ ELECTRICAL SPECIFICATIONS

Digital Communication	
Digital Interface	RS-485
Communication Protocol	Modbus
Power	
Power Consumption	0.25 W
Power Supply	DC 9-24 V, ≥1 A

■ ENVIRONMENTAL SPECIFICATIONS

Temperature	
Operating Temperature Range	0-50 °C (32-122 °F)
Mechanical & Environmental	
Ingress Protection	IP68
Dimensions	Φ36 mm × 265 mm, with protective cover (Φ1.42 in × 10.43 in)
Cable Length	10 m (32.8 ft) default, customizable
Housing Material	POM + 316L Stainless Steel (titanium alloy customizable)

■ COMMUNICATION PROTOCOLS

Digital Interface	RS-485
Communication Protocol	Modbus

■ ORDERING INFORMATION

Complete model number reference: **SX-CNLNA-111**

Measurement Range

1	0-100 mg/L
2	0-1,000 mg/L

Accuracy

1	±10% or ±0.5 mg/L (whichever is greater)
---	--

pH Measurement Range

1	4-10 pH
---	---------

Customized

D	Customized — specify requirements when ordering
---	---